



| Dimensionen / Dimensions mm (inch.) | |
|------------------------------------------|----------|
| D | d4 |
| b | |
| k | |
| d2 | |
| Anz./no | |
| Überwurfflansch Composite flange | -- |
| Bride folle | |
| Schmelze /Heat no: | |
| B-Nr: | |
| Fixflansch Fixed flange | 1.4408 |
| Bride fixe | |
| Schmelze /Heat no: | |
| B-Nr: | |
| Schwimmer / Schutzbalg Float / Bellow | 1.4571 |
| Flotteur / Soufflet | Perbunan |
| Schmelze /Heat no: | |
| B-Nr: | |

| | | | | | | | |
|-----------------------------------------------------------|---------------------------|---------------------------------------------------------|-----------|-------------------------------------------------------------|-----------|------------------------------------------------------|-------------------------|
| Typ Type Type | A 01 051 | Schaltmodul Switch module Module de commande | A | Flanschmodul Flange module Module de bride | 01 | Schwimmermodul Float module Module de flotteur | 051 |
| Betriebstemperatur Operating temp. Temp. de service | 0 to 120°C | Gehäusematerial Housing material Matériau boîtier | Aluminium | Druck / Nennweite Pressure / Bore Pression / Diamètre | PN 25 | Schaltdifferenz Operating diff. Différentiel | 12 mm |
| Umgebungstemp. Ambient temp. Temp. d'ambiance | 0 to 70°C | Kabeleinführung Cable entry Presse-étoupe | M20 x 1.5 | Norm Standard Norme | Besta | Dichte min. Density min. Densité min. | 0.75 kg/dm ³ |
| Schaltleistung Switch rating Pouvoir de coupure | 5A / 250VAC 5A / 30VDC | Schutzart Enclosure Cl. de protection | IP 65 | Dichtungsart Flange Facing Type d'étanchéité | Form C | Prüfdruck Test pressure Pression d'épreuve | 4 MPa (40 bar) |

| | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Order no. | |
| Stk./ pcs./quant. | |
| Date/Visa | 24.09.2008 / SI |
|  | |
| Besta AG, Ackerstrasse 45 CH-8610 Uster / Switzerland Fon +41 43 399 15 15 Fax +41 43 399 15 00 Email: info@besta.ch http://www.besta.ch | |
| | 010400/PH |