



U3...: Submersible level switch with 3 m cable

Dimensionen / Dimensions mm (ft.)		
Lk	3 m (9.84')	

Überwurfflansch Composite flange Bride folle	--
Schmelze /Heat no:	
B-Nr:	
Fixflansch Fixed flange Bride fixe	1.4408
Schmelze /Heat no:	
B-Nr:	
Schwimmer Float Flotteur	1.4571

Type Type Type	U3A 01 041	Schaltmodul Switch module Module de commande	U3A	Flanschmodul Flange module Module de bride	01	Schwimmermodul Float module Module de flotteur	041
Betriebstemperatur Operating temp. Temp. de service	-30 to 80°C	Gehäusematerial Housing material Matériau boîtier	Aluminium chromated	Nennndruck / -weite Nom. Pressure / - Diameter Pression - / Section Nominal	PN 25	Schaltdifferenz Operating diff. Différentiel	12 mm (0.47")
Umgebungstemp. Ambient temp. Temp. d'ambiance	-30 to 80°C	Kabeleinführung Cable entry Presse-étoupe	M20 x 1.5	Norm Standard Norme	Besta	Dichte min. Density min. Densité min.	0.700 kg/dm³
Schaltleistung Switch rating Pouvoir de coupure	5A / 250VAC 5A / 30VDC	Schutzart Enclosure Cl. de protection	IP 68	Dichtungsart Flange Facing Type d'étanchéité	Form C	Prüfdruck Test pressure Pression d'épreuve	40 bar

Order no.	
Stk./ pcs./quant.	
Date/Visa	28.02.2011 / SI

BESTA

Besta AG, Ackerstrasse 45
 CH-8610 Uster / Switzerland
 Phone +41 43 399 15 15
 Fax +41 43 399 15 00
 info@besta.ch
 www.besta.ch